

Version 3.1

Revision Date 12/14/2016

Print Date 02/28/2017

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name	:	A07699 ZC FOAMING GLS ZUFGC19A 20N19 STK
Material number	:	0000000001046502
Manufacturer or supplier's o	leta	lils
Company	:	Zep Inc.
Address	:	1310 Seaboard Industrial Blvd., NW Atlanta, GA 30318
Telephone	:	404-352-1680

Emergency telephone numbers

For SDS Information	:	Compliance Services 1-877-428-9937
For a Medical Emergency	:	877-541-2016 Toll Free - All Calls Recorded
For a Transportation	:	CHEMTREC: 800-424-9300 - All Calls Recorded.
Emergency		In the District of Columbia 202-483-7616

Recommended use of the chemical and restrictions on use

Recommended use : Glass Cleaner

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	Aerosol containing a liquefied gas
Colour	colourless
Odour	pleasant

GHS Classification

Gases under pressure	: Liquefied gas
GHS label elements	
Hazard pictograms	
Signal word	: Warning
Hazard statements	: H280 Contains gas under pressure; may explode if heated.
Precautionary statements	 Storage: P410 + P403 Protect from sunlight. Store in a well-ventilated place. Disposal: P501 Dispose of contents/ container to an approved waste disposal plant.



Version 3.1

Revision Date 12/14/2016

Print Date 02/28/2017

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration [%]
ethanol	64-17-5	>= 1 - < 5
butane	106-97-8	>= 1 - < 5
propan-2-ol	67-63-0	>= 1 - < 5
The second mean tensor of displaced with store and an		1-

The exact percentages of disclosed substances are withheld as trade secrets.

SECTION 4. FIRST AID MEASURES

General advice	:	Do not leave the victim unattended. Move out of dangerous area. Show this safety data sheet to the doctor in attendance.
If inhaled	:	If unconscious place in recovery position and seek medical advice. Consult a physician after significant exposure.
In case of skin contact	:	If skin irritation persists, call a physician. Wash off immediately with plenty of water for at least 15 minutes. If on clothes, remove clothes.
In case of eye contact	:	Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist. Rinse immediately with plenty of water for at least 15 minutes.
If swallowed	:	Keep respiratory tract clear. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. DO NOT induce vomiting unless directed to do so by a physician or poison control center. Take victim immediately to hospital.
Most important symptoms and effects, both acute and delayed	:	Effects may be delayed, symptoms may include minor eye or skin irritation. Overexposure may cause mild eye or skin irritation.
Notes to physician	:	Treat symptomatically. Symptoms may be delayed.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	:	Water spray jet
		Alcohol-resistant foam
		Carbon dioxide (CO2)
		Dry chemical



Version 3.1	Revision Date 12/14/2016	Print Date 02/28/2017
Unsuitable extinguishing media	: High volume water jet	
Specific hazards during firefighting	: Do not allow run-off from fire fightir courses.	ng to enter drains or water
Hazardous combustion products	: Carbon dioxide (CO2) Carbon monoxide Smoke	
Specific extinguishing methods	: Use extinguishing measures that a circumstances and the surrounding	
Further information	: Standard procedure for chemical fi Collect contaminated fire extinguis must not be discharged into drains Fire residues and contaminated fire be disposed of in accordance with For safety reasons in case of fire, separately in closed containments. Use a water spray to cool fully close	hing water separately. This e extinguishing water must local regulations. cans should be stored
Special protective equipment for firefighters	: Wear self-contained breathing app necessary.	paratus for firefighting if

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	 Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Environmental precautions	 Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for containment and cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Sweep up or vacuum up spillage and collect in suitable container for disposal.

SECTION 7. HANDLING AND STORAGE

Advice o	n safe handling	:	Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Do not breathe vapours or spray mist. Take precautionary measures against static discharges.
			Provide sufficient air exchange and/or exhaust in work rooms.



Version 3.1	Revision Date 12/14/2016	Print Date 02/28/2017
	Dispose of rinse water in accordance regulations. Always replace cap after use.	e with local and national
Conditions for safe storage	 BEWARE: Aerosol is pressurized. K exposure and temperatures over 50 or throw into fire even after use. Do red-hot objects. Keep container tightly closed in a dr place. Observe label precautions. Electrical installations / working mat- the technological safety standards. Keep in a dry, cool and well-ventilated 	°C. Do not open by force not spray on flames or y and well-ventilated erials must comply with
Materials to avoid	: Oxidizing agents	

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type	Control	Basis
Components	0/10/110.	(Form of	parameters /	Dasis
		exposure)	Permissible	
		expectate)	concentration	
ethanol	64-17-5	TWA	1,000 ppm	ACGIH
		TWA	1,000 ppm	NIOSH REL
			1,900 mg/m3	
		TWA	1,000 ppm	OSHA Z-1
			1,900 mg/m3	
		TWA	1,000 ppm	OSHA P0
			1,900 mg/m3	
		STEL	1,000 ppm	ACGIH
		PEL	1,000 ppm	CAL PEL
			1,900 mg/m3	
butane	106-97-8	TWA	800 ppm	NIOSH REL
			1,900 mg/m3	
		TWA	800 ppm	OSHA P0
			1,900 mg/m3	
		PEL	800 ppm	CAL PEL
			1,900 mg/m3	
propan-2-ol	67-63-0	TWA	200 ppm	ACGIH
		STEL	400 ppm	ACGIH
		TWA	400 ppm	NIOSH REL
			980 mg/m3	
		ST	500 ppm	NIOSH REL
			1,225 mg/m3	
		TWA	400 ppm	OSHA Z-1
			980 mg/m3	
		TWA	400 ppm	OSHA P0
			980 mg/m3	
		STEL	500 ppm	OSHA P0
			1,225 mg/m3	
		PEL	400 ppm	CAL PEL
			980 mg/m3	
		STEL	500 ppm	CAL PEL

SAFETY DATA SHEET



ANTEND TO EDAMING OF STUEGO 10A 20N10 STK

ersion 3.1		Revision Date 1			T III Date	02/28/2017
				1,225 mg/m	n3	
Biological occupat	tional exposure	limits				
Component	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissi concentra	
PROPAN-2-OL	67-63-0	Acetone	Urine	End of shift at end of workwee k	40 mg/l	ACGIH BE
Engineering meas	sures :e	ffective ventilation	on in all proc	essing area	IS	
Personal protectiv	e equipment					
Respiratory protecti	v	: Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.				
Hand protection Remarks		: The suitability for a specific workplace should be discussed with the producers of the protective gloves.				
Eye protection		: Eye wash bottle with pure water Safety glasses				
Skin and body prote	C	n : Impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place.				
Hygiene measures : Wash hands before breaks and at the end of workday. When using do not eat, drink or smoke. When using do not smoke.		ay.				

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

: Aerosol containing a liquefied gas	
: colourless	
: pleasant	
: No data available	
: 10 - 11	
: No data available	
: No data available	
:	
No data available	
: No data available	
: No data available	
: No data available	
	 pleasant No data available 10 - 11 No data available



Version 3.1	Revision Date 12/14/2016	Print Date 02/28/2017
Vapour pressure	: No data available	
Relative vapour density	: No data available	
Density	: 0.986 g/cm3	
Solubility(ies)		
Water solubility	: soluble in cold water, soluble in hot wa	ater
Partition coefficient: n- octanol/water	: No data available	
Auto-ignition temperature	: not determined	
Thermal decomposition	: No data available	
Viscosity		
Viscosity, kinematic	: No data available	

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Stable
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions Conditions to avoid	No decomposition if stored and applied as directed.Heat, flames and sparks. Extremes of temperature and direct sunlight.
Incompatible materials	: Oxidizing agents
Hazardous decomposition products	: Carbon oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Potential Health Effects

Aggravated Medical Condition Symptoms of Overexposure	None known.Effects may be delayed, symptoms may include minor eye or skin irritation.
Carcinogenicity:	
IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
OSHA	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.
NTP	No component of this product present at levels greater than or



Version 3.1	Revision Date 12/14/2016	Print Date 02/28/2017
	equal to 0.1% is identified as a known or a by NTP.	anticipated carcinogen
Acute toxicity		
Product:		
Acute oral toxicity	: Acute toxicity estimate : > 5,000 mg/kg Method: Calculation method	
Components:		
ethanol: Acute oral toxicity	: LD50 Oral Rat: 7,060 mg/kg	
Acute inhalation toxicity	: LC50 Rat: 124.7 mg/l Exposure time: 4 h	
butane: Acute inhalation toxicity	: LC50 Mouse: 1,237 mg/l Exposure time: 2 h	
	LC50 Rat: 1,355 mg/l	
propan-2-ol: Acute oral toxicity	: LD50 Oral Rat: 4,396 mg/kg Method: Calculation method	
Skin corrosion/irritation		
No data available		
Serious eye damage/eye irritatio	on	
No data available		
Respiratory or skin sensitisation		
No data available		
Germ cell mutagenicity		
No data available		
Carcinogenicity		
No data available		
Reproductive toxicity		
No data available		
ethanol: butane: propan-2-ol:		
STOT - single exposure		
No data available		
STOT - repeated exposure		
No data available		

SAFETY DATA SHEET



A07699 ZC FOAMING GLS ZUFGC19A 20N19 STK

Version 3.1

Revision Date 12/14/2016

Print Date 02/28/2017

Aspiration toxicity

No data available

Further information

Product:

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available **Bioaccumulative potential**

P	ra	hd	11	C	t۰
		~	u	<u>u</u>	ι.

Flouuci.	
Partition coefficient: n- octanol/water <u>Components:</u> butane : Partition coefficient: n- octanol/water	: Remarks: No data available : Pow: 2.89
Mobility in soil	
No data available	
Other adverse effects	
No data available Product:	
Regulation	40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances
Remarks	This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).
Additional ecological information	: No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues

: Do not dispose of waste into sewer.



Version 3.1	Revision Date 12/14/2016	Print Date 02/28/2017
	Do not contaminate ponds, waterw chemical or used container. Dispose of in accordance with loca	•
Contaminated packaging	: Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch	on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA): ORM-D, CONSUMER COMMODITY

Transportation Regulation: IMDG (Vessel): UN1950, AEROSOLS, 2.2, - Limited quantity

Transportation Regulation: IATA (Cargo Air): UN1950, AEROSOLS, 2.2, - Limited quantity

Transportation Regulation: IATA (Passenger Air): UN1950, AEROSOLS, 2.2, - Limited quantity

Transportation Regulation: TDG (Canada): UN1950, AEROSOLS, 2.2, - Limited quantity

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

SECTION 15. REGULATORY INFORMATION

TSCA list

: No substances are subject to a Significant New Use Rule. No substances are subject to TSCA 12(b) export notification requirements.

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : S	Sudden Release of Pressure Hazard
--------------------------	-----------------------------------

SARA 302 : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.



Version 3.1	Revision Date 12/14/2016 Print Date 02/28/			
SARA 313	: This material does not contain any ch known CAS numbers that exceed the reporting levels established by SARA	e threshold (De Minimis)		
California Prop 65	This product does not contain any chemicals known to State California to cause cancer, birth defects, or any other reproductive harm.			
The components of this product are reported in the following inventories:				
TSCA DSL	On TSCA Inventory All components of this product are on the Canadian DSL			


For information on the country notification status for other regions please contact the manufacturer's regulatory group.

Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

SECTION 16. OTHER INFORMATION

Further information



OSHA - GHS Label Information:

Hazard pictograms		
Signal word Hazard statements Precautionary state		er pressure; may explode if heated.
	Storage : Protect fr Disposal: Dispose	romsunlight. Store in a w ell-ventilated place. e of contents/ container to an approved w aste disposal plant.
X.	21	
Version:	3.1	
		10 / 11



Version 3.1

Revision Date 12/14/2016

Print Date 02/28/2017

Revision Date:	12/14/2016
Print Date:	02/28/2017

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.

Zep Inc. markets products under well recognized and established brand names such as Zep®, Zep Commercial®,Zep Professional®, Enforcer®, National Chemical[™], Selig[™], Misty®, Next Dimension[™], Petro®, i-Chem®, TimeMist®, TimeWick[™], MicrobeMax®, Country Vet®, Konk®, Original Bike Spirits®, Blue Coral®, Black Magic®, Rain-X®, Niagara National[™], FC Forward Chemicals®,Rexodan®, Mykal[™], and a number of private labeled brands.