

1. Identification

Product identifier Ultra-Clear Spray Glass Cleaner

Other means of identification

FIR No. 019761

Recommended use Glass Cleaner

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Company Name Ford Motor Company

Address Attention: SDS Information, P.O. Box 1899

Dearborn, Michigan 48121

USA

Telephone 1-800-392-3673

SDS Information 1-800-448-2063 (USA and Canada)

fordsds.com

Emergency telephone numbers

Poison Control Center: USA and Canada: 1-800-959-3673

INFOTRAC (Transportation): USA and Canada 1-800-535-5053

2. Hazard(s) identification

Physical hazards Gases under pressure Dissolved gas

Health hazards Not classified.

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Warning

Hazard statement Contains gas under pressure; may explode if heated.

Precautionary statement

Prevention Observe good industrial hygiene practices.

Response Wash hands after handling.

Storage Protect from sunlight. Store in a well-ventilated place.

Disposal Dispose of waste and residues in accordance with local authority requirements.

Hazard(s) not otherwise classified (HNOC) May cause irritation of respiratory tract. May irritate eyes and skin. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
PROPAN-2-OL		67-63-0	3 - 4
BUTANE		106-97-8	3

4. First-aid measures

Inhalation	If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Call a physician if symptoms develop or persist.
Skin contact	Wash off with soap and water. Get medical attention if irritation develops and persists.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention if irritation develops and persists.
Ingestion	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting.
Most important symptoms/effects, acute and delayed	Direct contact with eyes may cause temporary irritation.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed. Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also consider initial evacuation for 800 meters (1/2 mile) in all directions. ALWAYS stay away from tanks engulfed in flame. Move containers from fire area if you can do so without risk. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	Contents under pressure. Pressurized container may explode when exposed to heat or flame.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Avoid contact with eyes, skin, and clothing. Avoid inhalation of vapors or mists. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. Keep unnecessary personnel away. Keep out of low areas. Remove all possible sources of ignition in the surrounding area. Local authorities should be advised if significant spillages cannot be contained. Wear appropriate protective equipment and clothing during clean-up. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	<p>Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.</p> <p>Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.</p> <p>Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.</p>
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling	Avoid contact with eyes, skin, and clothing. Avoid breathing mist or vapor. Avoid prolonged exposure. Provide adequate ventilation. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Observe good industrial hygiene practices. Wear appropriate personal protective equipment. For personal protection, see Section 8 of the SDS.
Conditions for safe storage, including any incompatibilities	Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Stored containers should be periodically checked for general condition and leakage. Store away from incompatible materials (see Section 10 of the SDS). Store in accordance with local/regional/national/international regulation.

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
PROPAN-2-OL (CAS 67-63-0)	PEL	980 mg/m3 400 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value
BUTANE (CAS 106-97-8)	STEL	1000 ppm
PROPAN-2-OL (CAS 67-63-0)	STEL	400 ppm
	TWA	200 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
BUTANE (CAS 106-97-8)	TWA	1900 mg/m3 800 ppm
PROPAN-2-OL (CAS 67-63-0)	STEL	1225 mg/m3 500 ppm
	TWA	980 mg/m3 400 ppm

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
PROPAN-2-OL (CAS 67-63-0)	40 mg/l	Acetone	Urine	*

* - For sampling details, please see the source document.

Appropriate engineering controls

Use adequate ventilation to control airborne concentrations below the exposure limits/guidelines. If user operations generate a vapor, dust and/or mist, use process enclosure, appropriate local exhaust ventilation, or other engineering controls to control airborne levels below the recommended exposure limits/guidelines.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection

Suitable chemical protective gloves should be worn when the potential exists for skin exposure. The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other. Nitrile gloves are recommended.

Other

Wear appropriate chemical resistant clothing if applicable.

Respiratory protection

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, an approved respirator must be worn. Respirator selection, use and maintenance should be in accordance with the requirements of OSHA Respiratory Protection Standard 29 CFR 1910.134 and/or Canadian Standard CSA Z94.4.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state	Liquid.
Form	Aerosol.

Color	Clear.
Odor	Alcoholic.
Odor threshold	Not available.
pH	10 ASTM D1293
pH concentration	100 % v/v
Melting point/freezing point	Not available.
Initial boiling point and boiling range	< -0.4 °F (< -18 °C)
Flash point	-20.2 °F (-29.0 °C) PMCC
Evaporation rate	> 1 (Ether=1)
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	

Explosive limit - lower (%) 1.9 %

Explosive limit - upper (%) 12.7

Vapor pressure Not available.

Vapor density > 1 (AIR=1)

Relative density 0.95

Relative density temperature 68 °F (20 °C)

Solubility(ies)

Solubility (water) Not available.

Partition coefficient (n-octanol/water) Not available.

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Viscosity Not available.

Other information

Heat of combustion 2.95 kJ/g

VOC 8 %

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous reactions Hazardous polymerization does not occur.

Conditions to avoid Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition products Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause irritation to the respiratory system. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Prolonged inhalation may be harmful.

Skin contact Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.

Eye contact Direct contact with eyes may cause temporary irritation.

Ingestion May be harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity

Components	Species		Calculated/Test Results
BUTANE (CAS 106-97-8)			
Acute			
Inhalation			
LC50	Mouse		680 mg/l, 2 Hours
	Rat		658 mg/l, 4 Hours
PROPAN-2-OL (CAS 67-63-0)			
Acute			
Dermal			
LD50	Rabbit		12800 mg/kg
Oral			
LD50	Dog		4797 mg/kg
	Mouse		3600 mg/kg
			4.5 g/kg
	Rabbit		6410 mg/kg
			8 g/kg
			5.03 g/kg
	Rat		5045 mg/kg
			4.7 g/kg
Other			
LD50	Mouse		4477 mg/kg
			1509 mg/kg
	Rat		2735 mg/kg
			1099 mg/kg
Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.		
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.		
Respiratory or skin sensitization			
Respiratory sensitization	Not a respiratory sensitizer.		
Skin sensitization	This product is not expected to cause skin sensitization.		
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.		
Carcinogenicity	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.		
IARC Monographs. Overall Evaluation of Carcinogenicity			
Not listed.			
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.		
Specific target organ toxicity - single exposure	Not classified.		
Specific target organ toxicity - repeated exposure	Not classified.		
Aspiration hazard	Not an aspiration hazard.		
Chronic effects	Prolonged inhalation may be harmful.		
12. Ecological information			
Ecotoxicity	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.		
Ecotoxicity			
Components	Species		Calculated/Test Results
PROPAN-2-OL (CAS 67-63-0)			
Aquatic			
Fish	LC50	Bluegill (Lepomis macrochirus)	> 1400 mg/l, 96 hours

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

BUTANE	2.89
PROPAN-2-OL	0.05

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Incinerate the material under controlled conditions in an approved incinerator. Do not incinerate sealed containers. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code D001: Waste Flammable material with a flash point <140 F
The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

<Unspecified>

UN number	UN1950
UN proper shipping name	AEROSOLS
Transport hazard class(es)	
Class	2.2
Subsidiary risk	-
Label(s)	2.2
Packing group	Not available.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

IATA

<Unspecified>

UN number	UN1950
UN proper shipping name	AEROSOLS, NON-FLAMMABLE
Transport hazard class(es)	
Class	2.2
Subsidiary risk	-
Label(s)	2.2
Packing group	Not available.
Environmental hazards	No.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

IMDG

<Unspecified>

UN number	UN1950
UN proper shipping name	AEROSOLS
Transport hazard class(es)	
Class	2.2
Subsidiary risk	-
Packing group	Not available.
Environmental hazards	
Marine pollutant	No.
EmS	Not available.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to
Annex II of MARPOL 73/78 and
the IBC Code

Not established.

DOT



IATA; IMDG



15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

BUTANE (CAS 106-97-8)

Listed.

PROPAN-2-OL (CAS 67-63-0)

Listed.

SARA 304 Emergency release notification

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical

Yes

Classified hazard categories

Gas under pressure

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
PROPAN-2-OL	67-63-0	3 - 4

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

BUTANE (CAS 106-97-8)

Safe Drinking Water Act (SDWA)

Not regulated.

US state regulations

California Proposition 65



WARNING: This product can expose you to chemicals including ETHYLENE OXIDE, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

ETHYLENE OXIDE (CAS 75-21-8) Listed: July 1, 1987

California Proposition 65 - CRT: Listed date/Developmental toxin

ETHYLENE OXIDE (CAS 75-21-8) Listed: August 7, 2009

California Proposition 65 - CRT: Listed date/Female reproductive toxin

ETHYLENE OXIDE (CAS 75-21-8) Listed: February 27, 1987

California Proposition 65 - CRT: Listed date/Male reproductive toxin

ETHYLENE OXIDE (CAS 75-21-8) Listed: August 7, 2009

International Inventories

All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.

16. Other information, including date of preparation or last revision

Issue date 08-01-2018

Revision date 08-01-2018

Version 02

HMIS® ratings Health: 2
Flammability: 2
Physical hazard: 0

NFPA ratings Health: 2
Flammability: -
Instability: 0

Preparation Information and Disclaimer This document was prepared by FCSD-Toxicology, Ford Motor Company, Fairlane Business Park IV, 17225 Federal Drive, Allen Park, MI 48101, USA, based in part on information provided by the manufacturer. The information on this data sheet represents our current data and is accurate to the best of our knowledge as to the proper handling of this product under normal conditions and in accordance with the application specified on the packaging and/or technical guidance literature. Any other use of the product which involves using the product in combination with any other product or any other process is the responsibility of the user. To the extent that there are any differences between this product's Safety Data Sheet (SDS) and the consumer packaged product labels, the SDS should be followed.

Revision information This document has undergone significant changes and should be reviewed in its entirety.

Part number(s) ZC-23